

STEALTH unit



Specifications

- Maximum flow: 60 SCFM at 100 PSI
- Patented activated carbon 1st stage removes oil to 0.003 PPM
- Final filtration to 0.01 micron at 99.99998% efficiency
- Maximum pressure: 150 PSI, maximum temp: 125 ° F
- High flow 3/8" regulator/gauge, 0-160 PSI gauge
- 1/2" NPT inlet, 3/8" NPT outlet

Replacement parts

- 1st stage element: 6960-1
- 2nd stage element: 3C-060
- 1st stage auto drain: N32-95-979
- 2nd stage manual drain: PC-02
- Pressure gauge: PG-160
- Pressure regulator: R30
- 1/2" Ball Valve: BV-051

Benefits

- Patented Inverse-Flow® Technology
- Water, dirt, and oil removal
- Auto drain 1st stage
- Easy serviceability (no tools needed!)
- Snap-lock ring design
- Easy spin-on/spin-off design
- Heavy duty metal construction

Applications

- Paint booths
- Lacquer spraying
- Critical air tools
- Prep stations

CA PROPOSITION 65 WARNING



WARNING: Cancer and
Reproductive Harm
www.P65Warnings.ca.gov/product



(800) 521-9200



www.driair.com | www.rti-pbe.com



@RTIPBE



@rti_pbe



Removes: ● ●

1.0 micron • 60 SCFM • Brass Manual Petcock Drain



- 1/4"**
 - STEALTH 6900B** No Regulator
 - STEALTH 6950B** Regulator w/ Gauge
 - STEALTH 6952B** Regulator w/ Gauge, (2) 1/4" Outlets
- 3/8"**
 - STEALTH 3050B** Regulator w/ Gauge
 - STEALTH 3052B** Regulator w/ Gauge, (2) 3/8" Outlets

Replacement Element: 6950-1

Removes: ● ● ●

1.0 micron • 60 SCFM • Brass Manual Petcock Drain



- 1/4"**
 - STEALTH 6910B** No Regulator
 - STEALTH 6960B** Regulator w/ Gauge
 - STEALTH 6962B** Regulator w/ Gauge, (2) 1/4" Outlets
- 3/8"**
 - STEALTH 3060B** Regulator w/ Gauge
 - STEALTH 3062B** Regulator w/ Gauge, (2) 3/8" Outlets

Replacement Element: 6960-1

Removes: ● ●

0.01 micron • 60 SCFM • Brass Manual Petcock Drain



- 1/4"**
 - STEALTH 7000B** Regulator w/ Gauge
 - STEALTH 7800B** No Regulator
- 1/2"**
 - STEALTH 1000B** Regulator w/ Gauge
 - STEALTH 1500B** Regulator w/ Gauge and manifold
- 3/8"**
 - STEALTH 7030B** Regulator w/ Gauge

Replacement Element: 3C-060

Removes: ● ● ●

0.01 micron • 60 SCFM • 1st Stage: Automatic Float Drain
2nd Stage: Brass Manual Petcock Drain



- 3/8"** **STEALTH 6060B** Regulator w/ Gauge

1st Stage Replacement Element: 6960-1
2nd Stage Replacement Element: 3C-060

Note: All Stealth units feature 1/2" NPT Inlet, Max Pressure: 200 PSI, Max Temp: 125°F | Removal Key: ● Water ● Dirt ● Oil

CA PROPOSITION 65 WARNING



WARNING: Cancer and Reproductive Harm
www.P65Warnings.ca.gov/product



(800) 521-9200



www.driair.com | www.rti-pbe.com



@RTiPBE



@rti_pbe

